## MATERIAL SAFETY DATA SHEET

Manufacturer: Schaeffer Mfg. Company **Emergency Response Number:** Address: 102 Barton Street 314-865-4105 or **Address** St. Louis, MO 63104 800-325-9962 SECTION 1 - PRODUCT INFORMATION Chemical Family: Petroleum Hydrocarbons and additives Trade Name: #203B E.P. Industrial Machine Lube With Soluble Moly SAE 30 ISO 100 Formula: Proprietary Mixture **SECTION 2 – HAZARDOUS INGREDIENTS** COMPONENTS-CHEMICAL NAMES AND COMMON CAS **Exposure Limits** NAMES Number TVL PEL ppm mg/m<sup>3</sup> mg/m<sup>3</sup> ppm 100% Paraffin Base Oils 64742-65-0, 90-92 5 64742-54-7, 64742-57-0. 64742-62-7 Olefin Sulfide 1.2-1.5 NE NE CI Solvent Blue 98 74499-36-8 <.05 NE ΝE Molybdenum Di-2-Ethylhexyldithiophosphate 68958-92-9 <1 10 15 Section 3 - PHYSICAL DATA **Boiling Point:** >600°F/300°C .887 Specific Gravity: Vapor Pressure (mm, Hg): Not Determined % Volatile: Nil Vapor Density (Air = 1): Not Determined Not Determined Evaporation Rate: (=1) Solubility in Water: Insoluble Not Applicable pH: Appearance and Odor: Blue Green color, Strong odor **SECTION 4 - FIRE AND EXPLOSION HAZARD DATA** Flash Point (Method) °F/°C: 440°F/226.67°C C.O.C. Flammability Limits UEL & LEL ---- Not Determined (ASTM D-92) Extinguishing Media: Carbon dioxide foam, dry chemical foam, sand, earth, waterfog. Special Fire Fighting Procedures: For fires involving this material, do not enter any enclosed or confined space without protective equipment including self-contained breathing apparatus. Unusual Fire & Explosion Hazards: Dense Black smoke SECTION 5 - REACTIVITY HAZARD DATA STABILITY Hazardous Decomposition [ ] WILL [X] WILL NOT OCCUR [X] STABLE [ ]UNSTABLE Conditions to Avoid: High heat, high energy ignition sources Incompatibility (Mat. to avoid): Strong oxidizers and reducers Hazardous Decomposition Products: Oxides of carbon, sulfur and products of incomplete combustion Conditions to Avoid: None **SECTION 6 - HEALTH HAZARD DATA** Threshold Limit Value and Sources: 5.0/mg/m³ for oil mist. OSHA & ACGIH. Acute Effects of Overexposure: Nausea and Diarrhea. Tackiness agents in this product may possibly be coagulated by stomach acids. Ingestion: Eye Contact: Irritation and redness to eyes Skin Contact: Prolonged and repeated contact with the skin can cause irritation and redness to skin. Inhalation: Vapors can be given off under high heat conditions excessive breathing of vapors can cause irritation of the respiratory tract. CHRONIC EFFECTS OF OVEREXPOSURE: None currently known **Emergency and First Aid Procedures:** Swallowing: If conscious give 2 glasses of water to drink. Do not induce vomiting. Seek medical attention immediately. Skin: Wash skin thoroughly with soap and water. Launder contaminated clothing. Remove victim to fresh air. If breathing is labored administer oxygen. If breathing has stopped start artificial Inhalation: respiration immediately. Flush eyes with clear, cool, clean water for 15 minutes. Seek medical attention immediately Eyes: **SECTION 7 – SPILL OR LEAK PROCEDURES** Environmental Impact: This material is not expected to present any environmental problems other than those associated with oil spills. If spilled into a watercourse, call the Coast Guard Toll Free No. 800-424-8802 Procedures To Be Taken If Material Is Released or Spilled: Immediately absorb spilled material with absorbent clay or oil dril. Keep out of sewers and waterways. Shovel up and dispose of in approved waste container Waste Disposal Method: Dispose of at an approved waste or disposal site facility in accordance with all applicable federal, state and local laws and regulations. This product is not considered to be an RCRA hazardous waste **SECTION 8 - SPECIAL PROTECTION INFORMATION Respiratory Protection:** None required under ordinary conditions of use. No special requirement under ordinary conditions of use and with adequate ventilation. Ventilation: Eye Protection: Chemical goggles or face shield **Protective Clothing:** Oil resistant gloves.

Date Prepared: 4/30/04 OF-1049 Rev. (1999)

## **SECTION 9 – SPECIAL PRECAUTIONS**

Precautions To Be Taken In Handling and Storage: Do not store near heat, spark, flame or strong oxidizers. Keep containers closed when not in use.

Special Comments: Remove oil soaked clothing, launder before reuse. Wash skin thoroughly with soap and water after handling. Keep away from food and feed products

## SECTION 10 - ADDITIONAL HEALTH AND TOXICOLOGICAL DATA

HMIS & NFPA Ratings: Health = 1 Fire = 1 Reactivity = 0

This product does not contain any of the chemicals listed on the National Toxicology Program Annual Reports on Carcinogens, The International Agency for Cancer Research Monographs and OSHA's 1910.10 Subpart Z List.

This product does not contain any chemicals that are found on the State of California's Proposition 65 List for chemicals classified as potential reproductive or cancer causing agent.

This product does not contain any greater than 1% of any of the chemicals listed on the EPA's SARA Title III Section 302/304 and 313 list and CERCLA 102(a)

All of the components in this material are on the US TSCA Inventory. All components are in compliance with the Canadian Environmental Act

Although the information and recommendations set forth herein (hereafter referred to as information) are presented in good faith and believed to be accurate and factual as of the date hereof, Schaeffer Mfg. Company makes no representation as to the completeness or accuracy thereof. Information is supplied upon the condition that the person receiving the same will make their own determination as to its safety and suitability for their purposes prior to use. In no event will Schaeffer Mfg. Company be responsible for damages of any natures whatsoever resulting from the use or reliance upon information. No representation or warranty, either expressed or implied, of merchantability or fitness for a particular purpose is made with respect to information of the product to which the information refers.